


LiveShell Series Specifications Comparison Sheet



LiveShell.X

PC-less live streaming and recording at up to 1080/60p.

LiveShell X is a premium innovative live broadcast streaming device with HDMI input encoding at up to 1080/60p in H.265 and microSD card recording support, all without a PC.

USD 799

Max. Resolution	1080/60p (one stream or one recording)
Video Encoding	H.265/H.264
Audio Encoding	AAC-LC
Video Bit Rate	100kbps to 20Mbps
Audio Bit Rate	255kbps (Max.)
Simultaneous Streams	Max. 3 streams (+1 preview)
Recording Media	microSD (SDXC)
Recording Resolution	1080/60p (max.) (one recording)
Lower Thirds Support	✓
Transparent Lower Thirds	✓
Network Connectivity	Ethernet (10BASE-T / 100BASE-TX) Wi-Fi (IEEE 802.11a/b/g/n/ac)
Video Input Terminal	HDMI
Input Resolution	HDMI (1080p/60(59.94), 1080p/50, 1080p/30(29.97), 1080p/25, 1080p/24(23.976), 1080i/60(59.94), 1080i/50, 720p/60(59.94), 720p/50, 720p/30(29.97), 720p/25, 720p/24(23.976), 576p, 576i, 480p, 480i, VGA)*1
Audio Input Terminal	HDMI-IN / Stereo Line-in
Protocol Support	RTMP client / RTSP server mode
Battery Operating Time	Max. 6 hours battery life
Battery Replaceable/Rechargeable	Replaceable / Rechargeable
Size	W:102mm × D:100mm × H:42mm
Weight	350g (excluding battery), 480g (including battery)



LiveShell.PRO

Live HD streaming for professionals.

LiveShell PRO features HDMI and composite AV inputs for HD and SD live streaming. H.264 video at up to 10Mbps and 720/30p resolution is supported.

USD 449

Max. Resolution	720/30p
Video Encoding	H.264
Audio Encoding	AAC-LC
Video Bit Rate	100kbps to 10Mbps
Audio Bit Rate	255kbps (Max.)
Simultaneous Streams	1 stream
Recording Media	-
Recording Resolution	-
Lower Thirds Support	✓
Transparent Lower Thirds	-
Network Connectivity	Ethernet (10BASE-T / 100BASE-TX) Wi-Fi (IEEE 802.11a/b/g/n/ac)*2
Video Input Terminal	HDMI / Composite
Input Resolution	HDMI (1080i/60(59.94), 1080i/50, 720p/60(59.94), 720p/50, 576p, 576i, 480p, 480i, VGA)*1 Composite (NTSC/PAL)
Audio Input Terminal	HDMI-IN / Stereo Line-in / Stereo microphone-in
Protocol Support	RTMP client / RTSP server mode
Battery Operating Time	Max. 3 hours battery life
Battery Replaceable/Rechargeable	Replaceable / Rechargeable
Size	W:123mm × D:90mm × H:26mm
Weight	300g (excluding battery), 350g (including battery)



LiveShell.2

The world's most cost effective HD live streaming device.

Compact and lightweight, LiveShell 2 is designed for budget-conscious users. Featuring a HDMI input and support for up to 720/30p HD live streaming.

USD 299

Max. Resolution	720/30p
Video Encoding	H.264
Audio Encoding	AAC-LC
Video Bit Rate	100kbps to 10Mbps
Audio Bit Rate	255kbps (Max.)
Simultaneous Streams	1 stream
Recording Media	-
Recording Resolution	-
Lower Thirds Support	✓
Transparent Lower Thirds	-
Network Connectivity	Ethernet (10BASE-T / 100BASE-TX) Wi-Fi (IEEE 802.11a/b/g/n/ac)
Video Input Terminal	HDMI
Input Resolution	HDMI (1080p/30(29.97), 1080p/25, 1080p/24(23.976), 1080i/60(59.94), 1080i/50, 720p/60(59.94), 720p/50, 576p, 576i, 480p, 480i, VGA)*1
Audio Input Terminal	HDMI-IN
Protocol Support	RTMP client / RTSP server mode
Battery Operating Time	Max. 3.3 hours battery life
Battery Replaceable/Rechargeable	Unreplaceable / Rechargeable
Size	W:78mm × D:113mm × H:26mm
Weight	150g